

## **MAINTENANCE-FREE MOTORCYCLE BATTERY**


MX30-3-P (12V32Ah)















## **GENERAL FEATURES**

- Maintenance-free
- · Sealed and non-spillable AGM battery
- · Shipped pre-charged and ready to install

## **CHARACTERISTICS**

Item		Specifications
Nominal Voltage		12V
Nominal Capacity (10HR)		32Ah
Cold Cranking Perfor	mance Amps@0°F (-18	8°C) 480A
Dimension (±2mm)	Length	170mm (6.69inches)
	Width	132.5mm (5.22inches)
	Container Height	175mm (6.89inches)
	Total Height	175mm (6.89inches)
Battery (with acid)	Approx Weight	10.38kg (22.9lbs)
Terminal type		R
Battery type	MX Series	
Full Charge	Constant-Voltage Charge:	
	Initial charging currer	nt Less than 0.3C <sub>10</sub>
	Voltage	14.40V~15.00V at 25°C (77°F)
	Charging time	15~18h
	Constant-Current Ch	arge:
	Charging current $0.1C_{10}$ , when charging voltage up to 14.40V, continue to charge 4h	
Floating Charge	Initial charging currer	nt Unlimited
	Voltage	13.50V~13.80V at 25°C (77°F)
Capacity affected by Temperature	40°C (104°F)	106%
	25°C (77°F)	100%
	0°C (32°F)	86%
	-15°C (5°F)	65%



Leoch International Technology Ltd.

www.leoch.com

Leoch Batteries Pte Ltd

www.leoch.sg

Leoch Battery Corporation

www.leochamericas.com

Leoch Europe S.A.



<sup>\*</sup>Values are subject to variation of +/- 5% in normal manufacturing processes.